

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

	REVISIONS						
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED		
1		released for production.	3/12/2015	RJC	JAG		
2	15-0193	-3 CH'D DIM WAS Ø1.50 ▼6.00 IS Ø1.5 ▼6.00.	8/5/2015	RJC	JAG		
3	16-0110	UPDATED TO NEW STANDARD1 CH'D DIM WAS ϕ 2.520 IS ϕ 2.52 $$ 8.00 +.1000.	8/18/2016	DEW	JAG		
4	16-0234	-3 CH'D DIM WAS Ø2.25 S.F. RBT18522-5 IS Ø2.25 +.0001 (S.F. RBT18522-5), ADDED ENGRAVE T/N NOTE.	11/28/2016	DPD	JAG		





DART

TITLE


DWG NO.


MAIN ROTOR HUB ADAPTER RBT18522-D


	ASSY ASSY P.O.				_ UNIT					DRAWN BY:	CLOUGH		.015 x 45° OR .015R 2. DIMENSIONAL LIMITS APPLY		
	QTY	ASSY QTY	B/O	Part #	QTY	Description	Material	B/O INFORMATION OR SPECIFICATIONS	PG.	CHECKED:	DUERFELD	DT	AFTER PLA	TING	
ļ										OPPS APPR:	ANDERSC	ON	ASME Y14.5	F DIM AND TOL PER 5M-2009	
				-1	1	SLEEVE ADAPTER	6061 / 7075		2	QA APPR:	LINDSAY			USED ON MODEL	
				-3	1	VERTICLE SUPPORT	6061 / 7075		3	APPROVED:	GILBERT			BELL 429	
Ī			B/O	-5	2	CUP POINT SET SCREW	S.S.	3/8-16 UNC X 3/4 (MCMASTER-CARR #92313A622)	1	SCALE	1:4	ATE 3/1	11/2015	SHEET 1 OF 3	

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

		REVISIONS			
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
3	16-0110	-1 CH'D DIM WAS Ø2.520 IS Ø2.52 ▼ 8.00 +.1000.	8/18/2016	DEW	JAG










TITLE


MAIN ROTOR HUB ADAPTER


DWG NO.		RBT185	522-D-1	REV 4			
MAT'L 6061	7075			S OTHERWISE SPECIFIED			
HEAT TREAT			.XXX ± .005	NSIONS ARE IN INCHES FRACTIONS ± 1/8			
	R ANODIZE		.XX ± .01 .X ± .1	ANGLES ±.5° SURFACES = 125/			
SPEC MIL-A	-8625, TYPE	II, CLASS I	1. BREAK ALL SHARP EDGES				
DRAWN BY:	CLOUGH	1	.015 x 45° (OR .015R NAL LIMITS APPLY			
CHECKED:	DUERFE	LDT	AFTER PLA	ATING			
OPPS APPR:	ANDERS	SON	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009				
QA APPR:	LINDSAY	/	USED ON MODEL				
APPROVED:	GILBERT			BELL 429			
SCALE	1:4	DATE 3/1	1/2015	SHEET 2 OF 3			

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

	REVISIONS						
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED		
2	15-0193	-3 CH'D DIM WAS Ø1.50 ▼ 6.00 IS Ø1.5 ▼ 6.0.	8/5/2015	RJC	JAG		
4		-3 CH'D DIM WAS Ø2.25 S.F. RBT18522-5 IS Ø2.25 +.0001 (S.F. RBT18522-5), ADDED ENGRAVE T/N NOTE.	11/28/2016	DPD	JAG		







DART

MAIN ROTOR HUB ADAPTER

DWG NO.		RBT185	522-D-3				
MAT'L 6061 / HEAT TREAT	7075		UNLESS OTHERWISE SPECIFIE DIMENSIONS ARE IN INCHES XXX + .005 FRACTIONS ± 1/8				
FINISH CLEA	R ANODIZE		.XX ± .01 .X ± .1		25/		
SPEC MIL-A	-8625, TYPE	II, CLASS I	1. BREAK ALL SHARP EDGES				
DRAWN BY: CLOUGH			.015 x 45° OR .015R - 2. DIMENSIONAL LIMITS APPLY				
CHECKED:	DUERFE	LDT	AFTER PLA				
OPPS APPR:	ANDERS	SON	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009				
QA APPR:	LINDSAY	,	USED ON MODEL				
APPROVED:	GILBERT			BELL 429			
SCALE	1:2	DATE 3/1	1/2015	SHEET 3 OF	3		

(-3)

VERTICLE SUPPORT